

Guarantee on product
material and workmanship
M/ET-PD-EN2025S2



Linear power output warranty

## **Product Features**



Advanced Technology

N-Type M10 wafer High density interconnect technology.



Increased Performance

Well-suited for use in environments characterized by high reflectivity, elevated temperatures, scarce land availability, and substantial labor expenses.



Increased Power Generation

Lower degradation, increased bifaciality, and lower temperature coefficient improves energy yields.



Increased Value

Increased efficiency results in decreased LCOE and BOS costs


www.elite-solar.com





Severe Weather Resilience


Certified to withstand: wind load (2400 Pascal) and snow load (5400 Pascal). Tested to withstand hail strikes of up to


WARRANTY INFORMATION











ELECTRICAL SPECIFICAT	IONS	STC : AM	/1.5 1000W/	m² 25°C.	NOCT: AM1.5	800W/m <sup>2</sup>	20°C	1m/s.	Test uncert	ainty for Pmax	c: ±3%.
Module Type E	ET-N772	TBH580GL	ET-N772	TBH585G	SL ET-N77	2TBH5900	GL ET	-N772	TBH595GI	L ET-N772	TBH600GL
STC/NOCT	STC	NOCT	STC	NOCT	STC	NOCT		STC	NOCT	STC	NOCT
Maximum Power -P <sub>mp</sub> (W)	580	436	585	440	590	444		595	447	600	451
Open Circuit Voltage -V <sub>oc</sub> (V)	52.08	49.48	52.28	49.67	52.48	49.86	į	52.68	50.05	52.88	50.24
Short Circuit Current -I <sub>sc</sub> (A)	13.72	11.07	13.76	11.10	13.81	11.14	:	L3.86	11.19	13.90	11.22
Maximum Power Voltage - V <sub>mp</sub> (V)	44.72	42.09	44.90	42.26	45.08	42.42	4	15.25	42.58	45.42	42.74
Maximum Power Current -I <sub>mp</sub> (A)	12.97	10.36	13.03	10.41	13.09	10.47	:	13.15	10.50	13.21	10.55
Module Efficiency STC-η <sub>m</sub> (%)	22.	5%	22.	6%	22	.8%		23.	.0%	2:	3.2%
Power Tolerance(W)					0~+3%						
Pmax Temperature Coefficient	t				-0.30%/°0	C					
Voc Temperature Coefficient					-0.22%/°0	2					
Isc Temperature Coefficient					+0.042%/	C.					
Fire Performance					Type 29(U	L)					
REAR SIDE POWER GAIN	l (ET-1	1772TBH5	590GL)								
Power Gain	:	10%		15%		20%	6		2	25%	
Maximum Power -P <sub>mp</sub> (W)	(	649		679		708			7	738	
Open Circuit Voltage -V <sub>oc</sub> (V)	5	2.48		52.48		52.4	8		5	2.48	
Short Circuit Current -I <sub>sc</sub> (A)	1	5.02		15.72		16.4	0		1	7.08	
Maximum Power Voltage -V <sub>mp</sub> (	(V) 4	5.08		45.08		45.0	8		4.	5.08	
Maximum Power Current -I <sub>mp</sub> (	(A) 1	4.40		15.06		15.7	1		10	6.37	
MECHANICAL SPECIFIC	ATION	C			ADDITO	TION	ONE	ITIO	NIC		

MECHANICAL SPECIFICATIONS					
External Dimension	2278 x 1134 x 35mm/89.69 x 44.65 x 1.38inch				
Weight	39.5kg/87.08lbs				
Solar Cells	N-Type Mono-crystalline(144pcs)				
Front Glass/Back Gla	ass 2.5mm/2.5mm(0.10inch)				
Frame	Anodized aluminium alloy				
Junction Box	IP68, 3 diodes				
Cable Length	4.0 mm²(12AWG), Portrait:200mm(+)/400mm(-) Or customized				
Connector	MC4 Compatible				
Power Bifaciality*	80%±10%				
Please contact info@elite-solar.com for technical support. This parameter is for reference only and it is not a part of the contracts.  The specifications are subject to change without prior potice.					

Dawey Diferiality*	000/ 1 100/	Siz	
Power Bifaciality*	80%±10%	We	
Please contact info@elite-solar.com for technical support. This parameter is for reference only and it is not a part of the contracts. The specifications are subject to change without prior notice.		vve	
		Pie	

APPLICATION CONDI	TIONS		
Maximum System Voltage	1500VDC		
Maximum Series Fuse Ratin	g 30A		
Operating Temperature	-40~+85 °C		
Nominal Operating Cell Ter	nperature 45±2°C		
Mechanical Load	5400Pa/2400Pa		
Hailstone Test	55mm hailstone at 33.9m/s		
PACKAGING			
Container	40' HQ		
Pieces per Pallet	31		
Size of packing (mm/inch)	2300*1120*1264/90.55*44.09*49.76		
Weight of packing (kg/lbs)	1224.5/2700		
Pieces per Container (Normal/Weight-limited area)	465		
-			